NSN 5306-01-522-1226

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-522-1226 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** Between 1.094 inches and 1.125 inches **Head Style:** Dished hexagon **Head Height:** Between 0.172 inches and 0.175 inches Width Between Flats: Between 0.367 inches and 0.375 inches **First Diameter From Head:** Between 0.170 inches and 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.593 inches and 0.598 inches **Point Style:** Cone **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Point Chamfer Angle:** Between 85.0 degrees and 95.0 degrees Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 **Material Specification:** Sae-ams-std 66 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Ams-qq-p-35 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-01-522-1226

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0