NSN 5306-01-522-5632

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-522-5632

Thread Class:

| 3a |
|--|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.590 inches |
| Fastener Length: |
| 2.340 inches |
| Head Style: |
| Double hexagon |
| Head Height: |
| 0.328 inches |
| Width Between Flats: |
| Between 0.865 inches and 0.877 inches |
| Grip Diameter: |
| 0.875 inches |
| End Application: |
| A-10 aircraft |
| Thread Diameter: |
| 0.563 inches |
| Grip Length: |
| 1.750 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Product Name: |
| Bolt, double hexagon, shear, alloy 718, for applications tp 900deg f |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams5662 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Ams-c-8837 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5306-01-522-5632

Shear Bolt - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A003b0