NSN 5306-01-522-6113

Shear Bolt - Page 1 of 2

Unjf

N/a

Shelf Life:



View Online at https://aerobasegroup.com/nsn/5306-01-522-6113 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.759 inches **Fastener Length:** 3.634 inches **Head Style:** Dished hexagon **Head Height:** 0.438 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Grip Diameter:** Between 0.889 inches and 0.890 inches **End Application:** Kc-135 aircraft **Thread Diameter:** 0.875 inches **Grip Length:** 2.875 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, tension, hex head, close tolerance, 6al-4v titanium alloy, short thread, reduced major thread diameter, nonlocking, 160 ksi ftu **Special Features:** 0156 oversize shank, restricted usage: for repair work only Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 assn standard single treatment response **Thread Series Designator:**

NSN 5306-01-522-6113

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0