NSN 5306-01-523-0904

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-523-0904

Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
1.071 inches			
Fastener Length:			
3.946 inches			
Head Style:			
Spline drive shear head			
Head Height:			
0.562 inches			
Extended Washer Diameter:			
Between 1.153 inches and 1.163 inches			
Extended Washer Thickness:			
0.090 inches			
Grip Diameter:			
Between 0.6230 inches and 0.6240 inches			
Head Minor Diameter:			
Between 0.673 inches and 0.688 inches			
End Application:			
C17a aircraft			
Thread Diameter:			
0.625 inches			
Grip Length:			
2.875 inches			
Thready Qty Per Inch (tpi):			
18			
Min. Tensile Strength (psi):			
220000 pounds per square inch			
Minimum Yield Strength:			
125000 pounds per square inch			
Surface Finish:			
32.0 microinches grip			
Product Name:			
Bolt, tension-spline drive, inconel718, 220-255 ksi ftu			
Material:			
Nickel alloy 718			
Material Specification:			
Ams5662 assn standard single material response			
Surface Treatment:			

Passivate

NSN 5306-01-523-0904

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0