
# NSN 5306-01-523-6822

Shear Bolt - Page 1 of 2



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# **Thread Length:**

Between 0.400 inches and 0.450 inches

#### Fastener Length:

0.550 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.430 inches and 0.439 inches

#### **Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**End Application:** 

B-52 ami mod

#### **Thread Diameter:**

0.250 inches

# Grip Length:

0.125 inches

# Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Product Name:**

Hex head, 160 ksi min tensile, long thread, a286, self-locking, nonlocking

#### Material:

Iron alloy 660

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# **Specification Data:**

81205-bacb30lm professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

---



# NSN 5306-01-523-6822

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

