## NSN 5306-01-524-0799



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-524-0799 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.694 inches **Fastener Length:** Between 1.491 inches and 1.521 inches **Head Style:** Dished hexagon **Head Height:** Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.678 inches and 0.690 inches **Grip Diameter:** 0.437 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole **Thread Diameter:** 0.437 inches **Grip Length:** 0.812 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.305 inches first hole **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-01-524-0799

Shear Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0