NSN 5306-01-524-0820

Shear Bolt - Page 1 of 2

Material Specification:



View Online at https://aerobasegroup.com/nsn/5306-01-524-0820

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.370 inches
Fastener Length:
3.370 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
Between 0.076 inches and 0.086 inches
Grip Diameter:
0.249 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Thread Diameter:
0.250 inches
Grip Length:
3.000 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.160 inches first hole and 0.180 inches first hole
Product Name:
Navy special project
Material:
Stainless steel

Ams5731 assn standard 1st material response and ams5732 assn standard 2nd material response or ams5737 assn standard 3rd material response

NSN 5306-01-524-0820

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Nas4003 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: