NSN 5306-01-524-7134

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-524-7134 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.389 inches **Fastener Length:** 2.389 inches **Head Style:** Dished hexagon **Head Diameter:** 2.389 inches **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** 2.000 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Ams 6415 assn standard 1st material response or ams 6322 assn standard 2nd material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5306-01-524-7134

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.