## NSN 5306-01-524-7134

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-524-7134

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

0.389 inches

#### Fastener Length:

2.389 inches

#### Head Style:

Dished hexagon

#### Head Diameter:

2.389 inches

#### Head Height:

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.430 inches and 0.439 inches

#### **Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

#### **Thread Diameter:**

0.250 inches

### Grip Length:

2.000 inches

#### Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

140000 pounds per square inch

#### Material:

Steel comp 4340 or steel comp 8740

## Material Specification:

Ams 6415 assn standard 1st material response or ams 6322 assn standard 2nd material response or mil-s-6049 military specification 2nd

material response

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5306-01-524-7134

Shear Bolt - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-s-6049 spec.

