NSN 5306-01-525-1221

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-525-1221

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.710 inches and 0.760 inches |
| Fastener Length: |
| 2.360 inches |
| |
| Head Style: |
| Head Height: |
| Between 0.250 inches and 0.265 inches |
| Width Between Flats: |
| |
| Between 0.741 inches and 0.752 inches |
| Grip Diameter: Between 0.4990 inches and 0.4995 inches |
| |
| End Application: |
| B-52 aircraft |
| Thread Diameter: |
| 0.500 inches |
| Grip Length: |
| 0.625 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 63.0 microinches grip |
| Product Name: |
| Bolt, close tolerance - hexagon head, titanium |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas678 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5306-01-525-1221

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0