NSN 5306-01-525-4985

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-525-4985

3a
Thread Direction:
Right-hand
Thread Length:
0.845 inches
Fastener Length:
2.407 inches
Head Style:
Spline extended washer
Head Height:
0.393 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
0.063 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Head Minor Diameter:
Between 0.485 inches and 0.500 inches
End Application:
C-17a aircraft
Thread Diameter:
0.438 inches
Grip Length:
1.568 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Minimum Yield Strength:
125000 pounds per square inch
Surface Finish:
32.0 microinches grip
Product Name:
Bolt, tension-spline drive, inconel 718, 220-255 ksi ftu
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate

NSN 5306-01-525-4985

Shear Bolt - Page 2 of 2



Surface Treatment Sp	pecification:
----------------------	---------------

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0