

View Online at <https://aerobasegroup.com/nsn/5306-01-526-0933>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.735 inches

Fastener Length:

2.685 inches

Head Style:

Hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Hole Diameter:

Between 0.106 inches and 0.116 inches

Grip Diameter:

Between 0.4935 inches and 0.4950 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

Between 1.865 inches and 1.885 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.469 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams 5737, a286 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type ii federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0