## NSN 5306-01-526-3902

Close Tolerance Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-526-3902

| Thread Direction:  |
|--|
| Right-hand   |
| Thread Length:   |
| 0.467 inches   |
| Fastener Length:   |
| Between 1.139 inches and 1.186 inches                            |
| Head Style:  |
| Spline drive shear head  |
| Head Height:   |
| 0.187 inches   |
|  |
| Grip Diameter:<br>0.311 inches                                   |
| Shank Unthreaded Hole Diameter:                                  |
|  |
| 0.076 inches first hole and 0.081 inches first hole              |
| Head Minor Diameter:   |
| 0.517 inches   |
| End Application:   |
| Fighter aircraft - first (f18 e/f)                               |
| Grip Length:   |
| Between 0.678 inches and 0.698 inches                            |
| Criticality Code Justification:                                  |
| Agav   |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.036 inches first hole  |
| Material:  |
| Steel comp xm-13   |
| Thread Series Designator:  |
| Unjf   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A003b0   |
|  |
|  |
|  |