NSN 5306-01-526-4286

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-526-4286

Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.813 inches **Fastener Length:** 1.563 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.420 inches and 0.440 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **End Application:** E-3a **Thread Diameter:** 0.500 inches **Grip Length:** 0.750 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Bolt, 12 point head, 220 ksi min tensile, 125 ksi min shear, nickel alloy 718 Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Aluminum

Thread Series Designator:

Unjf

NSN 5306-01-526-4286

Shear Bolt - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0