NSN 5306-01-526-4286

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-526-4286

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.813 inches
Fastener Length:
1.563 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.420 inches and 0.440 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
Between 0.113 inches and 0.133 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
End Application:
E-3a
Thread Diameter:
0.500 inches
Grip Length:
0.750 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Bolt, 12 point head, 220 ksi min tensile, 125 ksi min shear, nickel alloy 718
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Aluminum
Thread Series Designator:

Unjf

NSN 5306-01-526-4286

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

