NSN 5306-01-526-5563

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-526-5563 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.938 inches **Fastener Length: 3.438** inches **Head Style:** Bevel-conical **Head Diameter:** Between 1.040 inches and 1.050 inches **Head Height:** 0.625 inches **Internal Drive Style:** Hexagon **End Application:** B-52 aircraft **Thread Diameter:** 0.625 inches Width Across Flats: 0.500 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Product Name:** Bolt, internal wrenching, 160 ksi ftu, 96 ksi fsu Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5306-01-526-5563

Internal Wrenching Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.