NSN 5306-01-528-5816

Shoulder Bolt - Page 1 of 2

3a

20





Thread Class: Thread Direction: Right-hand Thread Length: 0.629 inches **Fastener Length:** 5.402 inches **Head Style:** Hexagon **Head Height:** Between 0.265 inches and 0.297 inches Width Between Flats: Between 0.740 inches and 0.752 inches **Shoulder Diameter:** 0.495 inches first shoulder and 0.499 inches first shoulder Shoulder Length: 3.520 inches first shoulder **End Application:** C-17 suppequip **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Shoulder Shape: Round first shoulder **Product Name:** Bolt, shoulder - hexagon head Material: Steel comp 8740 or steel comp 4140 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1297 professional/industrial association standard

NSN 5306-01-528-5816

Shoulder Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

