
## NSN 5306-01-529-4743

Shear Bolt - Page 1 of 2



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.399 inches Fastener Length: Between 0.946 inches and 0.976 inches **Head Style:** Spline extended washer **Head Height:** Between 0.195 inches and 0.215 inches **Extended Washer Diameter:** Between 0.349 inches and 0.359 inches **Extended Washer Thickness:** Between 0.017 inches and 0.037 inches Hole Diameter: Between 0.032 inches and 0.042 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches Head Minor Diameter: Between 0.235 inches and 0.250 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.552 inches and 0.572 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Round longitudinal hole Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Passivate

4



## NSN 5306-01-529-4743

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0