## NSN 5306-01-529-9598

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-529-9598

| The second secon |
|--|
| Thread Class:  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.444 inches and 0.494 inches  |
| Fastener Length:   |
| 1.781 inches   |
| Head Style:  |
| Dished hexagon   |
| Head Height:   |
| Between 0.156 inches and 0.171 inches  |
| Width Between Flats:   |
| Between 0.492 inches and 0.502 inches  |
| Grip Diameter:   |
| Between 0.3110 inches and 0.3120 inches  |
| End Application:   |
| C-135 aircraft   |
| Thread Diameter:   |
| 0.312 inches   |
| Grip Length:   |
| 1.312 inches   |
| Thready Qty Per Inch (tpi):  |
| 24   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Surface Finish:  |
| 32.0 microinches threads   |
| Product Name:  |
| Bolt, close tolerance  |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5731 assn standard single material response or ams5737 assn standard single material response   |
| Surface Treatment:   |
| Cadmium and chromate   |
| Surface Treatment Specification:   |
| Qq-p-416, type 2, class 2 federal specification single treatment response  |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas6705 professional/industrial association standard   |

## NSN 5306-01-529-9598

Shear Bolt - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0