

View Online at <https://aerobasegroup.com/nsn/5306-01-530-2445>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.659 inches

**Fastener Length:**

Between 2.294 inches and 2.324 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.327 inches and 0.347 inches

**Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Grip Diameter:**

Between 0.373 inches and 0.374 inches

**Head Minor Diameter:**

Between 0.423 inches and 0.438 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.615 inches and 1.635 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

20900 pounds per square inch

**Surface Finish:**

32.0 microinches bearing surface of head

**Special Features:**

Lubricant, solid film per as5272 type 1

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response or ams 5663 assn standard single material response or ams 5962 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0