NSN 5306-01-530-2445

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-530-2445 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.659 inches **Fastener Length:** Between 2.294 inches and 2.324 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.373 inches and 0.374 inches **Head Minor Diameter:** Between 0.423 inches and 0.438 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 20900 pounds per square inch Surface Finish: 32.0 microinches bearing surface of head **Special Features:** Lubricant, solid film per as5272 type 1 Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response or ams 5663 assn standard single material response or ams 5962 assn standard single material response **Thread Series Designator:**

N/a

Unjf

Shelf Life:

Unit Of Measure:

NSN 5306-01-530-2445

Shear Bolt - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A003b0