NSN 5306-01-530-7376

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-530-7376
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
3.656 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.311 inches and 0.312 inches
Single Shear Strength:
95000 pounds per square inch
End Application:
C-135 aircraft
Thread Diameter:
0.312 inches
Grip Length:
3.187 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Product Name:
Bolt, machine
Material:
Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or ams 6415 assn standard 2nd material response or mil-s-5000 military specification
3rd material response or mil-s-6049 military specification 4th material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5306-01-530-7376

Shear Bolt - Page 2 of 2



Specification Data:
80205-nas6605 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

. ...

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.