

View Online at <https://aerobasegroup.com/nsn/5306-01-531-3869>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

4.278 inches

Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4990 inches and 0.4995 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

End Application:

C-17a aircraft

Thread Diameter:

0.500 inches

Grip Length:

3.750 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.580 inches first hole

Surface Finish:

32.0 microinches threads

Product Name:

Bolt, tension, hex head, close tolerance, a 286 cres, short thread, reduced major thread dia, nonlocking, 160 ksi ftu

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0