# NSN 5306-01-531-4509

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-531-4509

## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.444 inches and 0.494 inches

### Fastener Length:

1.531 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.156 inches and 0.171 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3110 inches and 0.3120 inches

## Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

## **Thread Diameter:**

0.312 inches

# Grip Length:

1.062 inches

### Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

# Distance From Head Largest Bearing Surface To Shank Hole Center:

1.388 inches first hole and 1.438 inches first hole

## Product Name:

Bolt, hex head, close tolerance, a286 cres, long threads, nonlocking

## Material:

Iron alloy 660

# Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

## Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a



# NSN 5306-01-531-4509

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

