## NSN 5306-01-532-3831



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-532-3831 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.669 inches and 0.719 inches **Fastener Length:** Between 1.929 inches and 1.959 inches **Head Style:** Dished hexagon **Head Height:** Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.678 inches and 0.690 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Shank Unthreaded Hole Diameter:** 0.111 inches first hole **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.893 inches first hole and 2.243 inches first hole Surface Finish: 32.0 microinches bearing surface of head **Product Name:** Bolt, hex head Material: Iron alloy 660 **Surface Treatment:** Cadmium **Thread Series Designator:** Unjf Shelf Life:

N/a
Unit Of Measure:

## NSN 5306-01-532-3831

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0