## NSN 5306-01-532-4203

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand **Thread Length:**0.734 inches

**Thread Direction:** 

Fastener Length:

Spline extended washer

**Head Style:** 

Between 2.407 inches and 2.437 inches

За



View Online at https://aerobasegroup.com/nsn/5306-01-532-4203

Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Hole Diameter:
0.005 inches
Grip Diameter:
Between 0.373 inches and 0.374 inches
Head Minor Diameter:
Between 0.422 inches and 0.438 inches
Thread Diameter:
0.375 inches
Grip Length:
1.688 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
260000 pounds per square inch
Hole Configuration Style:
Round
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium

## NSN 5306-01-532-4203

Shear Bolt - Page 2 of 2



## **Surface Treatment Specification:**

Mil-c-8837, ty ii, cl2 military specification single treatment response

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas-21296 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.