NSN 5306-01-532-4670

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-532-4670

Thread Class:					
3a					
Thread Direction:					
Right-hand					
Thread Length:					
0.438 inches					
Fastener Length:					
Between 0.688 inches and 0.718 inches					
Head Style:					
Spline extended washer					
Head Height:					
Between 0.195 inches and 0.215 inches					
Extended Washer Diameter:					
Between 0.349 inches and 0.359 inches					
Extended Washer Thickness:					
Between 0.017 inches and 0.037 inches					
Grip Diameter:					
Between 0.1885 inches and 0.1995 inches					
Head Minor Diameter:					
Between 0.173 inches and 0.188 inches					
Thread Diameter:					
0.190 inches					
Grip Length:					
Between 0.240 inches and 0.260 inches					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
260000 pounds per square inch					
Hardness Rating:					
51.0 rockwell c and 54.0 rockwell c					
Material:					
Steel comp h11					
Material Specification:					
Ams6487 assn standard single material response					
Surface Treatment:					
Cadmium and chromate					
Surface Treatment Specification:					
Mil-c-8837, type 2 cl 2 military specification single treatment response					
Thread Series Designator:					
Unjf					
Shelf Life:					
N/a					

NSN 5306-01-532-4670

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.