NSN 5306-01-532-6258

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-532-6258

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.440 inches and 0.507 inches |
| Fastener Length: |
| 1.904 inches |
| Head Style: |
| Double hexagon |
| Head Height: |
| Between 0.247 inches and 0.267 inches |
| Width Between Flats: |
| Between 0.678 inches and 0.689 inches |
| Grip Diameter: |
| Between 0.4358 inches and 0.4367 inches |
| End Application: |
| A-10 |
| Thread Diameter: |
| 0.438 inches |
| Grip Length: |
| 1.438 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hardness Rating: |
| 46.0 rockwell c and 50.0 rockwell c |
| Surface Finish: |
| 32.0 microinches threads |
| Product Name: |
| Bolt |
| Material: |
| Steel comp h11 |
| Material Specification: |
| Ams 6485 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas 672 assn standard single treatment response |
| Thread Series Designator: |

Unjf

NSN 5306-01-532-6258

Shear Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0