

View Online at <https://aerobasegroup.com/nsn/5306-01-535-4370>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.454 inches

**Fastener Length:**

1.454 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**End Application:**

C-17a aircraft

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.000 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Surface Finish:**

32.0 microinches bearing surface of head

**Product Name:**

Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread dia., nonlocking, 160 ksi ftu

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard 1st material response or ams 5737 assn standard all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2 federal specification 1st treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6306 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0