NSN 5306-01-536-2155

Shear Bolt - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5306-01-536-2155

| view Offilite at https://aerobasegroup.com/nsn/3300-01-330-2133 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.323 inches |
| Fastener Length: |
| 1.011 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.090 inches and 0.105 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Hole Diameter: |
| Between 0.180 inches and 0.200 inches |
| Grip Diameter: |
| Between 0.1845 inches and 0.1850 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 0.688 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel comp 4140 or steel comp 4340 or steel comp 8740 |
| Material Specification: |
| Ams6349 assn standard single material response or ams6484 assn standard single material response or ams6332 assn standard single |
| material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type ii, class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |

NSN 5306-01-536-2155

Shear Bolt - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A003b0