NSN 5306-01-536-4431

Close Tolerance Bolt - Page 1 of 2



| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| Between 0.330 inches and 0.360 inches |
| Fastener Length: |
| Between 0.830 inches and 0.860 inches |
| Head Style: |
| Fillister countersunk |
| Head Diameter: |
| Between 0.265 inches and 0.272 inches |
| Head Height: |
| 0.042 inches |
| Grip Diameter: |
| Between 0.2021 inches and 0.2026 inches |
| End Application: |
| F/a-18 aircraft |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.490 inches and 0.510 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Criticality Code Justification: |
| Agav |
| Product Name: |
| Bolt, 100 degrees reduced head, gear drive recess, inconel 718 (125 ksi shear), 0.0156 inch oversize |
| Special Features: |
| Internal drive recess per nas 1800 |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Mil-l-87132, type 1, gr b military specification single treatment response |

Supplementary Features:

Cotter pin hole 0.070 inch diameter at the tip of the bolt 0.106 inch from the end

NSN 5306-01-536-4431

Close Tolerance Bolt - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |

Mil-std (military Standard):

Mil-I-87132 spec.