## NSN 5306-01-536-4434

Close Tolerance Bolt - Page 1 of 2





| Thread Class:  |
|--|
| За   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.410 inches and 0.440 inches  |
| Fastener Length:   |
| Between 0.910 inches and 0.940 inches  |
| Head Style:  |
| Fillister countersunk  |
| Head Diameter:   |
| Between 0.265 inches and 0.272 inches  |
| Head Height:   |
| 0.057 inches   |
| Grip Diameter:   |
| Between 0.2646 inches and 0.2651 inches  |
| End Application:   |
| F/a-18 aircraft  |
| Thread Diameter:   |
| 0.250 inches   |
| Grip Length:   |
| Between 0.490 inches and 0.510 inches  |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Criticality Code Justification:  |
| Agav   |
| Product Name:  |
| Bolt, 100 degrees reduced head, gear drive recess, inconel 718 (125 ksi shear), 0.0156 inch oversize |
| Special Features:  |
| Internal drive recess per nas 1800   |
| Material:  |
| Nickel alloy 718   |
| Material Specification:  |
| Ams 5662 assn standard single material response  |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Mil-I-87132, type 1, gr b military specification single treatment response                           |
|  |

## **Supplementary Features:**

0.076 inch diameter cotter pin hole at the tip of the bolt 0.106 inch from the end

## NSN 5306-01-536-4434

Close Tolerance Bolt - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-I-87132 spec.