

View Online at <https://aerobasegroup.com/nsn/5306-01-536-7987>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.412 inches

**Fastener Length:**

0.935 inches

**Head Style:**

Double hexagon

**Head Height:**

0.300 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Hole Diameter:**

0.037 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Single Shear Strength:**

125000 pounds per square inch

**End Application:**

C17-a aircraft

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.375 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Product Name:**

Bolt-tension, double hexagon, flanged, 220 ksi min uts, inco 718, 900 degrees fmax

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0