NSN 5306-01-539-5678

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-539-5678 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** 1.078 inches **Head Style:** Hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches Washer Quantity: **End Application:** C-17a spt eqmt **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Primary Washer Outside Diameter:** 0.600 inches **Primary Washer Style:** Finishing **Primary Washer Material Thickness:** 0.032 inches **Product Name:** Bolt, assembly - support equipment, cres **Special Features:** FURN-IS-HED-WITH Material: Steel comp 303se stand-off **Material Specification:** Qq-s-764, cond a federal specification single material response stand-off **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5306-01-539-5678

Assembled Washer Bolt - Page 2 of 2



| Thread Series Designator: |
|------------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| Mil-std (military Standard): |

Mil-s-5059 spec.