
# NSN 5306-01-539-8359

Shear Bolt - Page 1 of 2



**Thread Class:** 3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

0.589 inches

# Fastener Length:

0.864 inches

Head Style:

Spline extended washer

Head Height:

Between 0.302 inches and 0.322 inches

#### **Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

#### **Extended Washer Thickness:**

Between 0.035 inches and 0.055 inches

#### **Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

#### Head Minor Diameter:

Between 0.360 inches and 0.375 inches

**End Application:** 

F-22 raptor

# Thread Diameter:

0.313 inches

#### Grip Length:

0.250 inches

Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

220000 pounds per square inch

#### **Product Name:**

Bolt, tension spline

# **Special Features:**

Dry film lubricant per mil-l-46010, type i

Material:

Nickel alloy 718

# **Material Specification:**

Ams5662 assn standard 1st material response or ams5663 assn standard 2nd material response

### Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response



# NSN 5306-01-539-8359

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

