## NSN 5306-01-540-3348

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand
Thread Length:
0.484 inches
Fastener Length:

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-540-3348

1.458 inches
Head Style:
Spline extended washer
Head Height:
Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.026 inches and 0.036 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Head Minor Diameter:
Between 0.318 inches and 0.324 inches
End Application:
C-17a aircraft
Thread Diameter:
0.250 inches
Grip Length:
0.938 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches grip
Product Name:
Bolt, spline drive - inconel 718, 180-220 ksi ftu
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

## NSN 5306-01-540-3348

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0