## NSN 5306-01-541-3255

Shear Bolt - Page 1 of 2



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.813 inches **Fastener Length:** 4.313 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.420 inches and 0.440 inches Width Between Flats: Between 0.549 inches and 0.562 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **End Application:** B52h **Thread Diameter:** 0.5000 inches Grip Length: 3.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Product Name:** 12 point bolt Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response Surface Treatment: Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** 

Unjf



## NSN 5306-01-541-3255

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

