## NSN 5306-01-541-5238

Close Tolerance Bolt - Page 1 of 2



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.468 inches
Fastener Length:
1.343 inches
Head Style:
Spline extended washer
Head Height:
0.250 inches
Extended Washer Diameter:
0.465 inches
Extended Washer Thickness:
0.036 inches
Grip Diameter:
0.249 inches
Head Minor Diameter:
0.250 inches
End Application:
Fighter aircraft (f18 e/f); arr list code
Thread Diameter:
0.250 inches
Grip Length:
0.875 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
8536 pounds per square inch
Product Name:
Inavy: bolt, close tolerance; dwg: bolt - close tolerance, spline drive, flange head (145 ksi fsu) cres
Special Features:
Wrenching element number 10; undrilled shank
Material:
Stainless steel
Material Specification:
M+35 per ams 5758 or ams 5844 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:

ourrace freatment opecinication

Ams-qq-+35 assn standard single treatment response

## NSN 5306-01-541-5238

Close Tolerance Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0