NSN 5306-01-542-3094

Shear Bolt - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-01-542-3094

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 0.763 inches Fastener Length: 3.466 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches Head Minor Diameter: Between 0.485 inches and 0.500 inches **Thread Diameter:** 0.437 inches Grip Length: 2.688 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:**

Cadmium and chromate

NSN 5306-01-542-3094

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Mil-c-8837 ty2 cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.