
## NSN 5306-01-542-3362

Shear Bolt - Page 1 of 2





Thread Class:

3a

**Thread Direction:** 

Right-hand

Thread Length:

0.495 inches

Fastener Length:

Between 1.735 inches and 1.755 inches

Head Style:

Spline extended washer

Head Height:

Between 0.240 inches and 0.260 inches

#### **Extended Washer Diameter:**

Between 0.460 inches and 0.470 inches

#### **Extended Washer Thickness:**

Between 0.026 inches and 0.046 inches

#### **Grip Diameter:**

Between 0.248 inches and 0.249 inches

#### Head Minor Diameter:

Between 0.235 inches and 0.250 inches

## Thread Diameter:

0.250 inches

Grip Length:

Between 1.240 inches and 1.260 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

220000 pounds per square inch

#### Material:

Nickel alloy 718

#### **Material Specification:**

Ams5662 assn standard single material response and ams5663 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

Shelf Life:

N/a

### Unit Of Measure:

--

# NSN 5306-01-542-3362

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

