NSN 5306-01-542-3420

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-542-3420

inread Length:
0.763 inches
Fastener Length:
1.216 inches
Head Style:
Spline extended washer
Head Height:
Between 0.383 inches and 0.403 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Head Minor Diameter:
Between 0.485 inches and 0.500 inches
Thread Diameter:
0.437 inches
Grip Length:
0.438 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Spline
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:

Cadmium and chromate

NSN 5306-01-542-3420

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
---------	------------------	----------------

Mil-c-8837 ty2 cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.