NSN 5306-01-545-2476

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-545-2476 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.334 inches **Fastener Length:** Between 0.933 inches and 0.983 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.275 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.345 inches **Extended Washer Thickness:** 0.064 inches **Grip Diameter:** Between 0.188 inches and 0.189 inches **End Application:** Ah-1w; bolt, tension, nickel alloy 718, 220 ksi, external wrenching, 12 point, flanged head **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220 megapascals **Product Name:** Inavy-bolt Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5306-01-545-2476

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0