NSN 5306-01-545-8339

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-545-8339

view Offilite at https://aerobasegroup.com/hai//0000-01-040-0000
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.455 inches
Fastener Length:
2.220 inches
Head Style:
Spline extended washer
Head Height:
0.250 inches
Extended Washer Diameter:
Between 0.470 inches and 0.480 inches
Extended Washer Thickness:
Between 0.026 inches and 0.046 inches
Grip Diameter:
Between 0.248 inches and 0.249 inches
Head Minor Diameter:
Between 0.235 inches and 0.250 inches
Thread Diameter:
0.250 inches
Grip Length:
1.765 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-e-6049 military
specification 4th material response or mil-s-8503 military specification 5th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, tii, cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-545-8339

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.