

View Online at <https://aerobasegroup.com/nsn/5306-01-545-8339>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.455 inches

Fastener Length:

2.220 inches

Head Style:

Spline extended washer

Head Height:

0.250 inches

Extended Washer Diameter:

Between 0.470 inches and 0.480 inches

Extended Washer Thickness:

Between 0.026 inches and 0.046 inches

Grip Diameter:

Between 0.248 inches and 0.249 inches

Head Minor Diameter:

Between 0.235 inches and 0.250 inches

Thread Diameter:

0.250 inches

Grip Length:

1.765 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

180000 pounds per square inch

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-e-6049 military specification 4th material response or mil-s-8503 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tii, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.