## NSN 5306-01-548-0254

Shear Bolt - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5306-01-548-0254

view Online at https://aerobasegroup.com/nsn/5306-01-548-0254	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.345 inches	
Fastener Length:	
Between 1.580 inches and 1.610 inches	
Head Style:	
Dished hexagon	
Head Height:	
0.110 inches	
Width Between Flats:	
Between 0.367 inches and 0.376 inches	
Grip Diameter:	
Between 0.1890 inches and 0.1895 inches	
Shank Unthreaded Hole Diameter:	
0.070 inches first hole	
Thread Diameter:	
0.1900 inches	
Grip Length:	
Between 1.240 inches and 1.260 inches	
hready Qty Per Inch (tpi):	
2	
Min. Tensile Strength (psi):	
95000 pounds per square inch	
Distance From Head Largest Bearing Surface To Shank Hole Center:	
2.681 inches first hole	
Material:	
Stainless steel	
Material Specification:	
Ams5731 assn standard 1st material response or ams5732 assn standard 2	and material response or ams5737 assn standard 3rd material
esponse or ams5853 assn standard 4th material response	
Surface Treatment:	
Cadmium	
Surface Treatment Specification:	
Qq-p-416, type ii class 2 federal specification single treatment response	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5306-01-548-0254

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

