

View Online at <https://aerobasegroup.com/nsn/5306-01-548-4013>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 1.298 inches and 1.328 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.311 inches and 0.312 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

0.938 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.194 inches first hole

Material:

Steel comp 4140 and steel comp 8740 and steel comp 4340 and steel comp 8735 and steel comp 6150

Material Specification:

Mil-s-5626 military specification 1st material response and mil-s-5000 military specification 2nd material response and mil-s-8503 military specification 3rd material response and mil-s-6098 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty2cl3 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.