

View Online at <https://aerobasegroup.com/nsn/5306-01-548-8993>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.343 inches and 0.390 inches

**Fastener Length:**

Between 1.281 inches and 1.328 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.102 inches and 0.134 inches

**Width Between Flats:**

Between 0.552 inches and 0.564 inches

**Grip Diameter:**

Between 0.373 inches and 0.374 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches and 0.116 inches

**Single Shear Strength:**

10500 pounds per square inch

**Thread Diameter:**

0.375 inches

**Grip Length:**

0.938 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.149 inches

**Special Features:**

Additional mdcl are mil-s-8503 and mil-s-8695

**Material:**

Steel comp 4140 and steel comp e4340 and steel comp 8740 and steel comp 8735 and steel comp 6150 and steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response and mil-s-5000 military specification 2nd material response and mil-s-6049 military specification 3rd material response and mil-s-6098 military specification 4th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, ty2cl2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.