

View Online at <https://aerobasegroup.com/nsn/5306-01-548-8993>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.343 inches and 0.390 inches

Fastener Length:

Between 1.281 inches and 1.328 inches

Head Style:

Hexagon

Head Height:

Between 0.102 inches and 0.134 inches

Width Between Flats:

Between 0.552 inches and 0.564 inches

Grip Diameter:

Between 0.373 inches and 0.374 inches

Shank Unthreaded Hole Diameter:

0.106 inches and 0.116 inches

Single Shear Strength:

10500 pounds per square inch

Thread Diameter:

0.375 inches

Grip Length:

0.938 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.149 inches

Special Features:

Additional mdcl are mil-s-8503 and mil-s-8695

Material:

Steel comp 4140 and steel comp e4340 and steel comp 8740 and steel comp 8735 and steel comp 6150 and steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response and mil-s-5000 military specification 2nd material response and mil-s-6049 military specification 3rd material response and mil-s-6098 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty2cl2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.