

View Online at <https://aerobasegroup.com/nsn/5306-01-550-4071>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.345 inches

**Fastener Length:**

Between 1.642 inches and 1.672 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

0.189 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.302 inches and 1.322 inches

**Thread Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

1600000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.493 inches first hole

**Material:**

Stainless steel

**Material Specification:**

Ams5731 assn standard 1st material response and ams35732 assn standard 2nd material response and ams 5737 assn standard 3rd material response and ams 5853 assn standard 4th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6703 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0