

View Online at <https://aerobasegroup.com/nsn/5306-01-550-5998>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.420 inches

**Fastener Length:**

1.815 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.265 inches

**Width Between Flats:**

0.250 inches

**Extended Washer Thickness:**

0.055 inches

**End Application:**

1520-01-471-6743, helicopter, search and rescue

**Thread Diameter:**

0.190 inches

**Grip Length:**

1.125 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.